NSN 5305-00-472-5430

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-472-5430 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.140 inches and 0.170 inches **Fastener Length:** Between 0.370 inches and 0.400 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.068 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.200 inches and 0.260 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 **Material Specification:** Qq-s-763 federal specification all material responses or 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-472-5430

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0