NSN 5305-00-476-0779

Externally Relieved Body Screw - Page 1 of 2



, , , , , , , , , , , , , , , , , , , ,
View Online at https://aerobasegroup.com/nsn/5305-00-476-0779
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.265 inches
Fastener Length:
0.940 inches
Head Style:
Knurled no. 1
Head Diameter:
0.560 inches
Head Height:
0.300 inches
First Diameter From Head:
0.300 inches
Second Diameter From Head:
Between 0.139 inches and 0.149 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.080 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.500 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Special Features:
Cone point 90 degrees of angle
Material:
Steel comp 303 or steel comp 303se
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unf
Shelf Life:

N/a

NSN 5305-00-476-0779

Externally Relieved Body Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0