

View Online at <https://aerobasegroup.com/nsn/5305-00-476-1222>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.282 inches

Fastener Length:

1.000 inches

Head Style:

Flat chamfer

Head Diameter:

0.437 inches

Head Height:

0.125 inches

Shank Unthreaded Hole Diameter:

0.875 inches first hole

First Diameter From Head:

Between 0.248 inches and 0.249 inches

Second Diameter From Head:

Between 0.145 inches and 0.150 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.660 inches and 0.670 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.708 inches and 0.718 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.070 inches first hole

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Cadmium head

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.