## NSN 5305-00-476-2538

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-476-2538 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** 0.445 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** 0.077 inches **First Diameter From Head:** 0.093 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.320 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 90 degrees of angle Material: Steel comp 430f **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-00-476-2538

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.