NSN 5305-00-476-7423

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-476-7423 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.190 inches and 0.210 inches **Fastener Length:** Between 0.690 inches and 0.710 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.410 inches and 0.430 inches **Head Height:** Between 0.490 inches and 0.510 inches **First Diameter From Head:** Between 0.110 inches and 0.115 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.440 inches and 0.460 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project **Special Features:** Nonstandard point no. 3, 0.050 lg Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

NSN 5305-00-476-7423

Externally Relieved Body Screw - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A003b0