## NSN 5305-00-478-0346



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-478-0346 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.658 inches and 0.735 inches **Fastener Length:** Between 1.704 inches and 1.751 inches **Head Style:** Pan **Head Diameter:** Between 0.716 inches and 0.740 inches **Head Height:** Between 0.244 inches and 0.261 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A500d0

## NSN 5305-00-478-0346

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.