## NSN 5305-00-478-6632

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-478-6632 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.637 inches and 0.750 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.313 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Special Features:** Finish color black Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response

Unc

**Specification Or Standard:** 

**Thread Series Designator:** 

6 type

## NSN 5305-00-478-6632

Socket Head Cap Screw - Page 2 of 2



Shelf	Life:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.