## NSN 5305-00-478-9983

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-478-9983 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.210 inches and 0.277 inches **Fastener Length:** Between 0.720 inches and 0.736 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.376 inches and 0.385 inches **Grip Diameter:** Between 0.1885 inches and 0.1894 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 300000 pounds per square inch Hardness Rating: 55.0 rockwell c and 58.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches threads Material: Vanadium alloy **Material Specification:** Vasco jet m-a fscm 87665 mfr ref single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5305-00-478-9983

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0