

View Online at <https://aerobasegroup.com/nsn/5305-00-479-0016>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.423 inches and 0.473 inches

Fastener Length:

Between 1.995 inches and 2.025 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.531 inches and 0.558 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.312 inches

Grip Length:

Between 1.552 inches and 1.572 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Countersink Angle:

60.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Bearing surface of head grooved to 0.394 in. Min 0.396 in. Maximum dia, 0.092 in. Min 0.097 in. Maximum distance from top of head

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0