## NSN 5305-00-479-0016

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-479-0016 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.423 inches and 0.473 inches **Fastener Length:** Between 1.995 inches and 2.025 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.531 inches and 0.558 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.552 inches and 1.572 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Countersink Angle:** 60.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Bearing surface of head grooved to 0.394 in. Min 0.396 in. Maximum dia, 0.092 in. Min 0.097 in. Maximum distance from top of head Material: Steel comp h11 **Material Specification:** Ams6485 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** 

Unf

Shelf Life:

**Thread Series Designator:** 

Ams 2416 assn standard all treatment responses

N/a

## NSN 5305-00-479-0016

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0