NSN 5305-00-479-4080

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-479-4080 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 0.875 inches **Head Style:** Flat chamfer **Head Diameter:** 0.375 inches **Head Height:** 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5305-00-479-4080

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.