

View Online at <https://aerobasegroup.com/nsn/5305-00-480-1827>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.845 inches and 0.875 inches

Fastener Length:

Between 2.100 inches and 2.120 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.977 inches and 1.000 inches

Head Height:

Between 0.490 inches and 0.500 inches

Shoulder Diameter:

0.7460 inches first shoulder and 0.7480 inches first shoulder

Shoulder Length:

1.245 inches first shoulder and 1.255 inches first shoulder

Single Shear Strength:

16600 pounds per square inch

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Width Across Flats:

0.375 inches

Thready Qty Per Inch (tpi):

11

Min. Tensile Strength (psi):

140000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 43.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0