## NSN 5305-00-480-1827

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-480-1827

view Offilite at https://aerobasegroup.com/hist//0000-00-400-1027
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.845 inches and 0.875 inches
Fastener Length:
Between 2.100 inches and 2.120 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.977 inches and 1.000 inches
Head Height:
Between 0.490 inches and 0.500 inches
Shoulder Diameter:
0.7460 inches first shoulder and 0.7480 inches first shoulder
Shoulder Length:
1.245 inches first shoulder and 1.255 inches first shoulder
Single Shear Strength:
16600 pounds per square inch
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
0.375 inches
Thready Qty Per Inch (tpi):
11
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Shoulder Shape:
Round first shoulder
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unc

## NSN 5305-00-480-1827

Shoulder Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0