NSN 5305-00-480-3580

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-480-3580 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.300 inches **Fastener Length:** Between 5.170 inches and 5.200 inches **Head Style:** Flat countersunk **Head Diameter:** 0.230 inches **First Diameter From Head:** Between 0.132 inches and 0.138 inches **Second Diameter From Head:** Between 0.092 inches and 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.048 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 4.950 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Steel comp 416 **Material Specification:**

Astm a582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

NSN 5305-00-480-3580

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-f-14072 spec.