Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-480-3580

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.250 inches and 0.300 inches
Fastener Length:
Between 5.170 inches and 5.200 inches
Head Style:
Flat countersunk
Head Diameter:
0.230 inches
First Diameter From Head:
Between 0.132 inches and 0.138 inches
Second Diameter From Head:
Between 0.092 inches and 0.098 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.048 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
4.950 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Countersink Angle:
Between 80.0 degrees and 82.0 degrees
Externally Relieved Body Diameter Quantity:
2
Product Name:
Navy special project
Material:
Steel comp 416
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, finish e300 military specification single treatment response

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.