## NSN 5305-00-480-4022

Machine Screw - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5305-00-480-4022



## 3a **Thread Direction: Right-hand Thread Length:** Between 0.046 inches and 0.187 inches Fastener Length: Between 0.172 inches and 0.219 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.241 inches and 0.250 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification all treatment responses **Thread Series Designator:** Unc **Specification Data:** 80205-nas1096 professional/industrial association standard Shelf Life: N/a Unit Of Measure:

## **Demilitarization:**

No

---

## NSN 5305-00-480-4022

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

