## NSN 5305-00-481-6966

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-481-6966 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.571 inches **Fastener Length:** Between 1.265 inches and 1.311 inches **Head Style:** Pan **Head Diameter:** Between 0.594 inches and 0.615 inches **Head Height:** Between 0.188 inches and 0.203 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 63.0 microinches grip **Product Name:** Navy special project Material: Steel comp e4340 **Material Specification:** Mil-s-5000, cond c military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** P.S.13145 type 2 cl 3 fscm 76301 mfr ref single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-00-481-6966

Close Tolerance Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.