NSN 5305-00-481-6992

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-481-6992 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.341 inches **Fastener Length:** Between 0.489 inches and 0.519 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Sι 32 M Tit Th Sp 80 Sł

Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r54520
Material Specification:
Nas621, comp 6al-4v assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1134 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-00-481-6992

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0