
NSN 5305-00-481-8943

Socket Head Cap Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.309 inches and 0.375 inches Fastener Length: Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.154 inches and 0.161 inches **Head Height:** Between 0.095 inches and 0.099 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.099 inches Width Across Flats: Between 0.078 inches and 0.079 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty2, cl3 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life: N/a Unit Of Measure:

NSN 5305-00-481-8943

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

