

View Online at <https://aerobasegroup.com/nsn/5305-00-482-6873>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.182 inches and 0.192 inches

**Fastener Length:**

Between 0.484 inches and 0.516 inches

**Head Style:**

Knurled no. 2

**Head Diameter:**

Between 0.307 inches and 0.317 inches

**Head Height:**

Between 0.172 inches and 0.202 inches

**First Diameter From Head:**

Between 0.073 inches and 0.083 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.183 inches and 0.193 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Point style no. 6 dim. 0.120 in. Min 0.130 in. Maximum long, 0.062 in. Min 0.078 in. Maximum dia, point angle 59.0 degree min, 61.0 degree max

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, finish e300 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.