## NSN 5305-00-482-6873

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-482-6873 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.182 inches and 0.192 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Knurled no. 2 **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.172 inches and 0.202 inches **First Diameter From Head:** Between 0.073 inches and 0.083 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.183 inches and 0.193 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point style no. 6 dim. 0.120 in. Min 0.130 in. Maximum long, 0.062 in. Min 0.078 in. Maximum dia, point angle 59.0 degree min, 61.0 degree max Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-00-482-6873

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.