NSN 5305-00-483-9466

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-483-9466

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.309 inches and 0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.134 inches and 0.140 inches
Head Height:
Between 0.083 inches and 0.086 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.086 inches
Width Across Flats:
Between 0.0781 inches and 0.0791 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 and steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Material Specification:
66 federal standard all material responses
66 federal standard all material responses Surface Treatment:
Surface Treatment:
Surface Treatment: Passivate
Surface Treatment: Passivate Surface Treatment Specification:
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc

N/a

NSN 5305-00-483-9466

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0