## NSN 5305-00-484-0822

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-484-0822 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.182 inches and 0.222 inches **Fastener Length:** Between 0.522 inches and 0.542 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.073 inches and 0.079 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.320 inches and 0.340 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-484-0822

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0