Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-484-0822

hread Class:	
a	
hread Direction:	
light-hand	
hread Length:	
etween 0.182 inches and 0.222 inches	
astener Length:	
etween 0.522 inches and 0.542 inches	
lead Style:	
Pan	
lead Diameter:	
etween 0.205 inches and 0.219 inches	
lead Height:	
etween 0.070 inches and 0.080 inches	
irst Diameter From Head:	
etween 0.073 inches and 0.079 inches	
vistance From Largest Bearing Surface Of Head To End Of First Diameter:	
etween 0.320 inches and 0.340 inches	
nternal Drive Style:	
Offset cruciform (torque set)	
hread Diameter:	
.112 inches	
hready Qty Per Inch (tpi):	
0	
xternally Relieved Body Diameter Quantity:	
laterial:	
on alloy 660	
laterial Specification:	
ms 5735 assn standard single material response	
Surface Treatment:	
assivate	
surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
hread Series Designator:	
Inc	
helf Life:	
l/a	
Init Of Measure:	
emilitarization:	

NSN 5305-00-484-0822

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

