

View Online at <https://aerobasegroup.com/nsn/5305-00-484-6250>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.070 inches and 0.080 inches

Fastener Length:

Between 0.070 inches and 0.080 inches

Head Style:

Button

Head Diameter:

Between 0.104 inches and 0.114 inches

Head Height:

Between 0.023 inches and 0.026 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.060 inches

Width Across Flats:

Between 0.035 inches and 0.036 inches

Thready Qty Per Inch (tpi):

80

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.