

View Online at <https://aerobasegroup.com/nsn/5305-00-484-9810>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.750 inches

**Fastener Length:**

Between 0.969 inches and 1.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.150 inches and 0.163 inches

**Width Between Flats:**

Between 0.428 inches and 0.438 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Minimum Yield Strength:**

30000 pounds per square inch

**Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 385 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, cl 2 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.