# NSN 5305-00-485-0915

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-485-0915

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.291 inches and 0.341 inches
Fastener Length:
Between 0.613 inches and 0.643 inches
Head Style:
Fillister
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.133 inches and 0.150 inches
Hole Diameter:
0.064 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Hole Quantity:
Drilled
Thready Qty Per Inch (tpi):
28 Nin Tanaila Strongth (api):
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating: 36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style: Round
Surface Finish:
32.0 microinches threads Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037 Surface Treatment:
Cadmium and chromate

## NSN 5305-00-485-0915

Close Tolerance Screw - Page 2 of 2



#### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### Thread Series Designator:

Unjf

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A003b0