NSN 5305-00-485-2376

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-485-2376 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.434 inches and 0.465 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.092 inches and 0.112 inches **Second Diameter From Head:** Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.085 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.535 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

N/a

Unc

Shelf Life:

Thread Series Designator:

NSN 5305-00-485-2376

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0