

View Online at <https://aerobasegroup.com/nsn/5305-00-485-8493>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.251 inches and 0.301 inches

Fastener Length:

Between 2.261 inches and 2.291 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.328 inches and 0.385 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.060 inches first hole and 0.080 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

Between 1.990 inches and 2.010 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

100.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.134 inches first hole and 2.184 inches first hole

Surface Finish:

32.0 microinches threads

Material:

Titanium alloy uns r54520

Material Specification:

Nas621, comp 6al-4v assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0