NSN 5305-00-485-8493

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-485-8493

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.251 inches and 0.301 inches |
| Fastener Length: |
| Between 2.261 inches and 2.291 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.328 inches and 0.385 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Shank Unthreaded Hole Diameter: |
| 0.060 inches first hole and 0.080 inches first hole |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.990 inches and 2.010 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 2.134 inches first hole and 2.184 inches first hole |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Titanium alloy uns r54520 |
| Material Specification: |
| Nas621, comp 6al-4v assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-00-485-8493

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

