NSN 5305-00-486-0476



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-486-0476 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.185 inches and 0.195 inches **Fastener Length:** Between 0.502 inches and 0.512 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.370 inches and 0.390 inches **Head Height:** Between 0.108 inches and 0.118 inches **Shoulder Diameter:** 0.186 inches first shoulder and 0.189 inches first shoulder **Shoulder Length:** 0.312 inches first shoulder and 0.322 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.033 inches first hole and 0.043 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 40 **Hardness Rating:** 32.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 0.389 inches first hole and 0.399 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 416 or steel comp 416f **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-00-486-0476 Shoulder Screw - Page 2 of 2



Fiig:

A003b0