

View Online at <https://aerobasegroup.com/nsn/5305-00-486-2093>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.350 inches and 0.400 inches

Fastener Length:

Between 1.735 inches and 1.765 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.577 inches and 0.635 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Unthreaded Hole Diameter:

0.066 inches first hole and 0.086 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.312 inches

Grip Length:

Between 1.365 inches and 1.385 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

100.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.606 inches first hole and 1.656 inches first hole

Surface Finish:

32.0 microinches threads

Material:

Titanium alloy uns r54520

Material Specification:

Nas621, comp 6al-4v assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0