## NSN 5305-00-486-2106

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-486-2106

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.350 inches and 0.400 inches
Fastener Length:
Between 3.235 inches and 3.265 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.577 inches and 0.635 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Shank Unthreaded Hole Diameter:
0.066 inches first hole and 0.086 inches first hole
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 2.865 inches and 2.885 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
100.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
3.106 inches first hole and 3.156 inches first hole
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r54520
Material Specification:
Nas621, comp 6al-4v assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-00-486-2106

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

