NSN 5305-00-486-2106

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-486-2106 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.400 inches **Fastener Length:** Between 3.235 inches and 3.265 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.577 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.066 inches first hole and 0.086 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 2.865 inches and 2.885 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 3.106 inches first hole and 3.156 inches first hole **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r54520 **Material Specification:** Nas621, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

_.

Unit Of Measure:

NSN 5305-00-486-2106

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0