

View Online at <https://aerobasegroup.com/nsn/5305-00-486-2362>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.291 inches and 0.341 inches

**Fastener Length:**

Between 3.051 inches and 3.081 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.449 inches and 0.507 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.066 inches first hole and 0.086 inches first hole

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 2.740 inches and 2.760 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

100.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.925 inches first hole and 2.975 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Titanium alloy uns r54520

**Material Specification:**

Nas 621, 6al-4v assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0