NSN 5305-00-486-2596

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-486-2596

3a Thread Direction: Right-hand
Right-hand
Thread Length:
Between 0.843 inches and 0.893 inches
Fastener Length:
Between 2.353 inches and 2.383 inches
Head Style:
Flat countersunk
Head Diameter:
Between 1.007 inches and 1.034 inches
Grip Diameter:
Between 0.6235 inches and 0.6245 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.625 inches
Grip Length:
Between 1.490 inches and 1.510 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Countersink Angle:
60.0 degrees
Surface Finish:
32.0 microinches threads
Special Features:
Bearing surface of head grooved to 0.769 in. Min, 0.771 in. Maximum dia, 0.155 in. Min, 0.160 in. Maximum from top of head
Material:
Steel comp h11
Material Specification:
Ams6485 assn standard single material response
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard all treatment responses
Thread Series Designator:
Unf
Shelf Life:
N/a

NSN 5305-00-486-2596

Close Tolerance Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0