

View Online at <https://aerobasegroup.com/nsn/5305-00-486-2596>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.843 inches and 0.893 inches

Fastener Length:

Between 2.353 inches and 2.383 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.007 inches and 1.034 inches

Grip Diameter:

Between 0.6235 inches and 0.6245 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.625 inches

Grip Length:

Between 1.490 inches and 1.510 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Countersink Angle:

60.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Bearing surface of head grooved to 0.769 in. Min, 0.771 in. Maximum dia, 0.155 in. Min, 0.160 in. Maximum from top of head

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0