

View Online at <https://aerobasegroup.com/nsn/5305-00-486-3565>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.382 inches and 0.418 inches

**Fastener Length:**

Between 5.528 inches and 5.588 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.235 inches and 0.255 inches

**Head Height:**

Between 0.132 inches and 0.156 inches

**First Diameter From Head:**

Between 0.139 inches and 0.145 inches

**Second Diameter From Head:**

Between 0.159 inches and 0.165 inches

**Third Diameter From Head:**

Between 0.250 inches and 0.270 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.927 inches and 0.947 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 5.024 inches and 5.054 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 5.118 inches and 5.148 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

3

**Special Features:**

Color red and furnished with one flat washer

**Material:**

Steel comp 303 or steel comp 430

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0