
NSN 5305-00-487-4803

Socket Head Cap Screw - Page 1 of 1





2a Thread Direction: Right-hand Thread Length: Between 0.074 inches and 0.181 inches Fateuer Length: Between 0.219 inches and 0.250 inches Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Strige Comp 303 Surface Treatment: Passivate Thread Stries Designator: Unc Shelf Life: Na Dird Measure: Tread Stries Designator: Na Dird Measure: Na Dird Measure: Thread Stries Designator: Na Dird Measure: Thread Stries Designator: Na <	Thread Class:
Thread Direction: Right-hand Thread Length: Between 0.074 inches and 0.181 inches Fastner Length: Between 0.219 inches and 0.250 inches Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shell Life: N/a Unit Of Measure: No Fig:	
Right-hand Thread Length: Between 0.074 inches and 0.181 inches Fastener Length: Between 0.219 inches and 0.250 inches Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Oty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Ding I Measure: - Demilitarization: No Fig:	
Tread Length: Between 0.074 inches and 0.181 inches Fastener Length: Between 0.219 inches and 0.250 inches Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Stele comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit of Measure: - Temilitarization: No Fig:	
Between 0.274 inches and 0.181 inches Fastener Length: Between 0.219 inches and 0.250 inches Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Y Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
Fastener Length: Between 0.219 inches and 0.250 inches Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Stel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Between 0.219 inches and 0.250 inches Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Edween 0.249 inches and 0.279 inches Edween 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Juameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Head Style: Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Jameter: 0.138 inches Thread Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Flat countersunk Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Head Diameter: Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
Between 0.249 inches and 0.279 inches Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Locking Feature: Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: O.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Inc Dimilitarization: 	-
Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
32 Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Countersink Angle: Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Between 80.0 degrees and 82.0 degrees Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	32
Material:Steel comp 303Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Countersink Angle:
Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 80.0 degrees and 82.0 degrees
Surface Treatment: Passivate Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel comp 303
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Passivate
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A00360	Fiig:
A00350	A003b0