NSN 5305-00-487-4868

Close Tolerance Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-487-4868

| Thread Class: | |
|------------------------|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.251 inches | s and 0.301 inches |
| Fastener Length: | |
| Between 1.949 inches | s and 1.979 inches |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 0.328 inches | s and 0.385 inches |
| Grip Diameter: | |
| Between 0.1885 inche | es and 0.1895 inches |
| Internal Drive Style: | |
| Offset cruciform (torq | ue set) |
| Thread Diameter: | |
| 0.190 inches | |
| Grip Length: | |
| Between 1.678 inches | s and 1.698 inches |
| Thready Qty Per Inc | h (tpi): |
| 32 | |
| Min. Tensile Strengt | h (psi): |
| 160000 pounds per s | quare inch |
| Countersink Angle: | |
| Between 99.0 degree | s and 101.0 degrees |
| Surface Finish: | |
| 32.0 microinches thre | ads |
| Material: | |
| Titanium alloy | |
| Material Specificatio | on: |
| | assn standard single material response or ams4928 assn standard single material response or ams4967 assn |
| standard single mater | |
| Thread Series Desig | |
| Unjf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |