NSN 5305-00-487-4985

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-487-4985 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.341 inches **Fastener Length:** Between 2.051 inches and 2.081 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.066 inches first hole and 0.086 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.740 inches and 1.760 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.925 inches first hole and 1.975 inches first hole **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r54520 **Material Specification:** Nas 621, 6al-4v assn standard single material response **Thread Series Designator:** Unjf

Shelf Life: N/a Unit Of Measure:

NSN 5305-00-487-4985

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0