NSN 5305-00-487-5088

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-487-5088

Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
Between 0.267 inches and 0.334 inches			
Fastener Length:			
Between 1.527 inches and 1.574 inches			
Head Style:			
Flat countersunk			
Head Diameter:			
0.502 inches			
Grip Diameter:			
Between 0.2483 inches and 0.2492 inches			
Shank Unthreaded Hole Diameter:			
0.076 inches first hole and 0.084 inches first hole			
Internal Drive Style:			
Offset cruciform (torque set)			
Thread Diameter:			
0.250 inches			
Grip Length:			
Between 1.240 inches and 1.260 inches			
Thready Qty Per Inch (tpi):			
28			
Min. Tensile Strength (psi):			
220000 pounds per square inch			
Hardness Rating:			
46.0 rockwell c and 50.0 rockwell c			
Countersink Angle:			
Between 99.0 degrees and 101.0 degrees			
Distance From Head Largest Bearing Surface To Shank Hole Center:			
1.403 inches first hole and 1.433 inches first hole			
Material:			
Steel comp h11			
Material Specification:			
Ams6485 assn standard single material response			
Surface Treatment:			
Cadmium			
Surface Treatment Specification:			
Nas 672 assn standard single treatment response			
Thread Series Designator:			

Unjf

NSN 5305-00-487-5088

Close Tolerance Screw - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0