

View Online at <https://aerobasegroup.com/nsn/5305-00-487-5092>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.266 inches and 0.333 inches

Fastener Length:

Between 1.464 inches and 1.511 inches

Head Style:

Flat countersunk

Head Diameter:

0.502 inches

Grip Diameter:

Between 0.2483 inches and 0.2492 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.084 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 1.178 inches and 1.198 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.341 inches first hole and 1.371 inches first hole

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0