NSN 5305-00-487-5092

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-487-5092

view Offiline at https://aerobasegroup.com/hsh/0505-00-407-5052
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.266 inches and 0.333 inches
Fastener Length:
Between 1.464 inches and 1.511 inches
Head Style:
Flat countersunk
Head Diameter:
0.502 inches
Grip Diameter:
Between 0.2483 inches and 0.2492 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.084 inches first hole
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.341 inches first hole and 1.371 inches first hole
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:

Unjf

NSN 5305-00-487-5092

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0