NSN 5305-00-487-6355

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-487-6355 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.544 inches and 0.625 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Round **Head Diameter:** Between 0.193 inches and 0.211 inches **Head Height:** 0.086 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 430 or steel comp 303 or steel comp 303se **Screw Material Specification:** Mil-s-7720 military specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-764 federal specification 3rd material response or qq-s-764 federal specification 4th material response **Screw Surface Treatment: Passivate Thread Series Designator:** Unc **Specification Or Standard:** 1c style and 3 type **Departure From Cited Designator:** As mod by material and finish Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A500d0

No

NSN 5305-00-487-6355

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.