## NSN 5305-00-487-6464

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-487-6464 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.302 inches and 0.332 inches **Fastener Length:** Between 0.302 inches and 0.332 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 303 **Material Specification:** Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or astm a582 assn standard 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-00-487-6464

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0