## NSN 5305-00-488-4249

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-488-4249 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.087 inches and 0.092 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.469 inches and 0.500 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** C190000120, fscm 88818 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-488-4249

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0