

View Online at <https://aerobasegroup.com/nsn/5305-00-488-4378>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.733 inches and 1.874 inches

**Fastener Length:**

Between 1.859 inches and 1.906 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.105 inches and 0.120 inches

**Width Between Flats:**

Between 0.302 inches and 0.313 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

Between 26.0 rockwell c and 32.0 rockwell c

**Screw Material:**

Steel comp 4037 or steel comp 8630

**Screw Material Specification:**

Ams 6300 federal specification all material responses or mil-s-6050 military specification 2nd material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas1096 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6050 spec.