NSN 5305-00-488-5921

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-488-5921 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.194 inches and 1.318 inches **Fastener Length:** Between 1.313 inches and 1.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.231 inches and 0.279 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: Between 248.0 brinell standard and 341.0 brinell standard **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5735 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1102 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

NSN 5305-00-488-5921

Machine Screw - Page 2 of 2



Fiig:

A500d0