

View Online at <https://aerobasegroup.com/nsn/5305-00-488-5921>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.194 inches and 1.318 inches

**Fastener Length:**

Between 1.313 inches and 1.375 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.231 inches and 0.279 inches

**Internal Drive Style:**

Torque set

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

Between 248.0 brinell standard and 341.0 brinell standard

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5735 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1102 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0